

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : <b>A44B 19/16</b>	<b>A1</b>	(11) International Publication Number: <b>WO 98/06291</b> (43) International Publication Date: 19 February 1998 (19.02.98)
<p>(21) International Application Number: PCT/US97/14296</p> <p>(22) International Filing Date: 14 August 1997 (14.08.97)</p> <p>(30) Priority Data: 08/698,923 16 August 1996 (16.08.96) US</p> <p>(71) Applicant: TENNECO PACKAGING INC. [US/US]; 1603 Orrington Avenue, Evanston, IL 60204 (US).</p> <p>(72) Inventors: DOBRESKI, David, V.; 99 Country Downs Circle, Fairport, NY 14450 (US). MCMANUS, Michael, W.; 5 Woodneath Crescent, East Rochester, NY 14450 (US).</p> <p>(74) Agent: BLANKSTEIN, Michael, J.; Arnold, White &amp; Durkee, P.O. Box 4433, Houston, TX 77210 (US).</p>	<p>(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).</p> <p>Published With international search report.</p>	

(54) Title: END POSTS FOR PLASTIC ZIPPER

## (57) Abstract

A plastic bag comprises first and second opposing panels, a reclosable zipper, and a slider. The first and second opposing panels are fixedly connected to each other along a pair of sides and a bottom bridging the pair of sides. The reclosable zipper extends along a mouth formed opposite the bottom. The zipper includes a first track with a first profile and a second track with a second profile. The first and second profiles are releasably engageable to each other. The slider is slidably mounted to the zipper for movement between a closed position and an open position. The first and second profiles are engaged to each other while the slider is in the closed position, and the first and second profiles are disengaged from each other in response to movement of the slider from the closed position to the open position. To prevent the slider from going past the ends of the zipper and to provide adequate end strength that resists stresses applied to the profiles during normal use of the bag, end terminations in the form of posts pass through the male and female tracks adjacent to the ends of the zipper. To retain the posts on the zipper, each of the posts includes enlarged heads at its opposing ends.



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

## END POSTS FOR PLASTIC ZIPPER

## FIELD OF THE INVENTION

The present invention generally relates to reclosable plastic bags and, more particularly, to a reclosable plastic bag including a zipper having an obstruction in the form of a post extending through tracks of the zipper.

5

## BACKGROUND OF THE INVENTION

A reclosable plastic bag typically includes first and second opposing panels fixedly connected to each other along a pair of sides and a bottom bridging the pair of sides. The first and second panels are not fixedly connected along a mouth which is formed opposite to the sealed bottom. Rather, the bag is provided with a reclosable zipper extending along the mouth of the plastic bag. The zipper includes a male track and a female track. In reclosable plastic bags of the type disclosed in U.S. Patent No. 5,067,208 utilizing a slider to open the zipper, the male track typically includes a male profile and a first fin extending downward from the male profile. Likewise, the female track in such bags with sliders includes a female profile and a second fin extending downward from the female profile. The first and second fins are thermally fused to the inner surfaces of the respective first and second panels.

The male and female tracks are typically free of any plastic material above the male and female profiles in order to permit proper mounting and movement of the slider. The male and female profiles are releasably engageable to each other. When the slider is in a closed position, the male and female profiles are interlocked with each other. In response to moving the slider to an open position, the male and female profiles are disengaged from each other. Once the male and female profiles are disengaged from each other, access to the interior of the bag may be obtained by pulling the first and second panels apart at the mouth.

Opposite ends of the zipper are provided with end terminations. The end terminations perform the dual function of stops for the ends of the zipper to prevent the slider from going past the ends of the zipper and, in addition, they hold the male and female profiles together to resist stresses applied to the profiles during normal use of the plastic bag. In U.S. Patent No. 5,067,208, each end termination is in the form of a strap/clip that wraps over the top of the zipper. One end of the strap is provided

with a rivet-like member that penetrates through the zipper fins and into a cooperating opening at the other end of the strap. Other types of end terminations are disclosed in U.S. Patent Nos. 5,482,375, 5,448,807, 5,442,837, 5,405,478, 5,161,286, 5,131,121, and 5,088,971.

5

## SUMMARY OF THE INVENTION

The present invention provides end terminations for a zipper of a reclosable plastic bag. The plastic bag comprises first and second opposing panels fixedly connected to each other along a pair of sides and a bottom bridging the pair of sides.

10 The bag is provided with a reclosable zipper extending along a mouth formed opposite the sealed bottom of the plastic bag. The zipper includes a male track and a female track. The male track includes a male profile and a first depending fin extending downward from the male profile. Likewise, the female track includes a female profile and a second depending fin extending downward from the female  
15 profile. If the zipper is formed separately from the panels of the bag, the first and second depending fins are thermally fused to inner surfaces of the respective first and second panels. Alternatively, the zipper may be integrally formed with the panels of the bag.

A slider is slidably mounted to the zipper for movement between a closed  
20 position and an open position. The male and female profiles are engaged to each other while the slider is in the closed position. The male and female profiles are disengaged from each other in response to movement of the slider to the open position.

To prevent the slider from going past the ends of the zipper and to provide  
25 adequate end strength that resists stresses applied to the profiles during normal use of the bag, end terminations in the form of posts pass through the male and female tracks adjacent to the ends of the zipper. The posts may be inserted through either the profiles or fins of the zipper. To retain the posts on the zipper, each of the posts includes enlarged heads at its opposing ends. These enlarged heads may be formed by  
30 pressure, heat, or ultrasonic melting.

### BRIEF DESCRIPTION OF THE DRAWINGS

Other objects and advantages of the invention will become apparent upon reading the following detailed description and upon reference to the drawings in which:

- 5           FIG. 1 is an isometric view of a mouth portion of a reclosable plastic bag having an end post inserted through the profiles of a zipper;
- FIG. 2 is a front view of the bag mouth portion in FIG. 1;
- FIG. 3 is a sectional view taken generally along line 3-3 in FIG. 1;
- FIG. 4 is an isometric view of a mouth portion of a reclosable plastic bag
- 10          having an end post inserted through the depending fins of a zipper;
- FIG. 5 is a front view of the bag mouth portion in FIG. 4; and
- FIG. 6 is a sectional view taken generally along line 6-6 in FIG. 4.

            While the invention is susceptible to various modifications and alternative forms, a specific embodiment thereof has been shown by way of example in the

15          drawings and will herein be described in detail. It should be understood, however, that it is not intended to limit the invention to the particular forms disclosed, but on the contrary, the intention is to cover all modifications, equivalents, and alternatives falling within the spirit and scope of the invention as defined by the appended claims.

### 20           DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

            Turning now to the drawings, FIGS. 1-3 depict a mouth portion of a reclosable plastic bag embodying the present invention. The plastic bag comprises first and second opposing panels 12 and 14 fixedly connected to each other along a pair of sides 16 (only one shown in FIGS. 1 and 2) and a bottom bridging the pair of sides 16.

25          The bag is provided with a reclosable zipper 22 extending along the mouth portion, which is formed opposite the sealed bottom of the plastic bag.

            The zipper 22 includes a male track and a female track. The male track includes a male profile 24 and a first depending fin or flange 26 extending downward from the male profile 24. Likewise, the female track includes a female profile 28 and

30          a second depending fin or flange 30 extending downward from the female profile 28. If the zipper 22 is formed separately from the panels 12 and 14 of the bag, the first and second fins 26 and 30 are thermally fused to inner surfaces of the respective first and

second panels 12 and 14. Alternatively, the zipper 22 may be integrally formed with the panels 12 and 14 such that the first fin 26 is integrally formed with the first panel 12 and the second fin 30 is integrally formed with the second panel 14.

To assist in opening the plastic bag, a slider 32 is slidably mounted to the zipper 22 for movement between a closed position and an open position. In the closed position of the slider 32 shown in FIG. 2, the male and female profiles 24 and 28 are interlocked with each other. Movement of the slider 32 from the closed position in FIG. 2 toward the open position (see FIG. 1) disengages the male and female profiles 24 and 28 from each other and allows a user to gain access to the interior of the plastic bag. The slider 32 includes a separator finger 34 (FIG. 1) for disengaging the male and female profiles 24 and 28 from each other. Further details concerning the construction and operation of the zipper 22 and slider 32 may be obtained from U.S. Patent No. 5,067,208 to Herrington, Jr. et al., which is incorporated herein in its entirety by reference.

To prevent the slider 32 from going past the ends of the zipper 22 and to provide adequate end strength that resists stresses applied to the profiles 24 and 28 during normal use of the bag, end terminations in the form of plastic pins or posts 36 pass through the male and female tracks adjacent to the ends of the zipper 22. In one embodiment depicted in FIGS. 1-3, the posts 36 extend through the profiles 24 and 28. In another embodiment depicted in FIGS. 4-6, the posts 36 extend through the bag panels 12 and 14 below the profiles 24 and 28 and preferably extend through the fins 26 and 30 at preseal areas P of the zipper 22. Using an ultrasonic welder or heat bar, the preseal areas P are formed on the fins 26 and 30 and facing bag panels 12 and 14 at the ends of the zipper 22 to reduce the material thickness and prepare for a leakproof end termination.

The posts 36 are generally linear in configuration and have a substantially circular cross-section. Other cross-sectional shapes are possible. Prior to inserting the posts 36 through the zipper 22, the posts 36 have a generally uniform cross-section throughout their length except at the ends, which are preferably sharp enough to pierce and penetrate through the zipper 22. Alternatively, the posts 36 may be inserted through preformed holes in the zipper 22. The posts 36 are installed onto the zipper 22 by forcing the pointed posts 36 through the zipper 22 at the desired location. As

stated above, the posts 36 are inserted through the profiles 24 and 28 in the embodiment of FIGS. 1-3, while the posts 36 are inserted through the bag panels 12 and 14 and the fins 26 and 30 in the embodiment of FIGS. 4-6.

To retain the posts 36 on the zipper 22 in both embodiments, each of the posts 36 includes a pair of opposing enlarged heads 38 that are formed by pressure, heat, or ultrasonic melting after the posts 36 are inserted through the zipper 22. One of the enlarged heads 38 abuts the outer surface of the first panel 12 (FIG. 6) or male profile 24 (FIG. 3), and the other of the enlarged heads 38 abuts the outer surface of the second panel 14 (FIG. 6) or female profile 28 (FIG. 3). The posts 36 preferably have a length only slightly greater than the thickness of the region through which the posts 36 are inserted so that the heads 38 firmly secure the posts 36 to the zipper 22 and there is minimal or no movement of the posts 36 relative to the zipper 22.

The posts 36 may be molded from any suitable plastic, including but not limited to nylon, polypropylene, polystyrene, high-density polyethylene, Delrin, or ABS.

The posts 36 are advantageous in that, unlike straps that wrap over the top of the zipper, the posts 36 require a minimal amount of plastic material. At the same time, the posts 36 adequately perform the dual function of stops for the ends of the zipper 22 to prevent the slider 32 from going off past the end of the zipper 22 and they hold the profiles 24 and 28 together to resist stresses applied to the profiles through normal use of the bag.

While the present invention has been described with reference to one or more particular embodiments, those skilled in the art will recognize that many changes may be made thereto without departing from the spirit and scope of the present invention. Each of these embodiments and obvious variations thereof is contemplated as falling within the spirit and scope of the claimed invention, which is set forth in the following claims.



**WHAT IS CLAIMED IS:**

1. In a reclosable plastic bag including first and second opposing panels fixedly connected to each other along a pair of sides and a bottom bridging said pair of sides; a reclosable zipper extending along a mouth formed opposite said bottom, said zipper  
5 including a first track with a first profile and a second track with a second profile, said first and second profiles being releasably engageable to each other; and a slider slidably mounted to said zipper for movement between a closed position and an open position, said first and second profiles being engaged to each other while said slider is in said closed position, said first and second profiles being disengaged from each  
10 other in response to movement of said slider from said closed position to said open position, an end stop arrangement comprising:  
a post extending through said first and second tracks near one end of said zipper adjacent to one of said pair of sides, said post including a generally linear member and a pair of enlarged heads at opposite ends  
15 of said generally linear member, said pair of enlarged heads being disposed on opposite sides of said zipper for retaining said post on said zipper, said end stop arrangement being free of plastic material extending over a top of said zipper.
- 20 2. The end stop arrangement of claim 1, wherein said post extends through said first and second profiles.
3. The end stop arrangement of claim 1, wherein said post extends through said first and second panels below said first and second profiles.  
25
4. The end stop arrangement of claim 1, wherein said first track includes a first fin extending downward from said first profile and said second track includes a second fin extending downward from said second profile, and wherein said post extends through said first and second fins.  
30
5. The end stop arrangement of claim 1, wherein said post has a generally circular cross-section.

6. The end stop arrangement of claim 1, wherein said pair of enlarged heads abut said respective opposite sides of said zipper.
- 5 7. The end stop arrangement of claim 1, further including a second post extending through said first and second tracks near the other end of said zipper adjacent to the other of said pair of sides, said second post including a generally linear second member and a second pair of enlarged heads at opposite ends of said generally linear second member, said second pair of enlarged heads being disposed on said  
10 opposite sides of said zipper for retaining said second post on said zipper.
8. A reclosable plastic bag, comprising:  
first and second opposing panels fixedly connected to each other along a pair of sides and a bottom bridging said pair of sides;  
15 a reclosable zipper extending along a mouth formed opposite said bottom, said zipper including a first track with a first profile and a second track with a second profile, said first and second profiles being releasably engageable to each other;  
a slider slidably mounted to said zipper for movement between a closed  
20 position and an open position, said first and second profiles being engaged to each other while said slider is in said closed position, said first and second profiles being disengaged from each other in response to movement of said slider from said closed position to said open position; and  
25 an end stop arrangement including a first post extending through said first and second tracks near one end of said zipper adjacent to one of said pair of sides, said first post including a generally linear first member and a first pair of enlarged heads at opposite ends of said generally linear first member, said first pair of enlarged heads being disposed on opposite  
30 sides of said zipper for retaining said first post on said zipper, said end stop arrangement being free of plastic material extending over a top of said zipper.

9. The plastic bag of claim 8, wherein said first post extends through said first and second profiles.

5 10. The plastic bag of claim 8, wherein said first post extends through said first and second panels below said first and second profiles.

11. The plastic bag of claim 8, wherein said first track includes a first fin extending downward from said first profile and said second track includes a second  
10 fin extending downward from said second profile, and wherein said first post extends through said first and second fins.

12. The plastic bag of claim 11, wherein first and second fins are sealed to each other where said first post extends therethrough.

15

13. The plastic bag of claim 8, wherein said first post has a generally circular cross-section.

14. The plastic bag of claim 8, wherein said first pair of enlarged heads abut said  
20 respective opposite sides of said zipper.

15. The plastic bag of claim 8, wherein said end stop arrangement further includes a second post extending through said first and second tracks near the other end of said zipper adjacent to the other of said pair of sides, said second post including a generally  
25 linear second member and a second pair of enlarged heads at opposite ends of said generally linear second member, said second pair of enlarged heads being disposed on said opposite sides of said zipper for retaining said second post on said zipper.

16. In a reclosable plastic bag including first and second opposing panels fixedly  
30 connected to each other along a pair of sides and a bottom bridging said pair of sides; a reclosable zipper extending along a mouth formed opposite said bottom, said zipper including a first track with a first profile and a second track with a second profile, said

first and second profiles being releasably engageable to each other; and a slider slidably mounted to said zipper for movement between a closed position and an open position, said first and second profiles being engaged to each other while said slider is in said closed position, said first and second profiles being disengaged from each other in response to movement of said slider from said closed position to said open position, a method of stopping said slider at an end of said zipper adjacent one of said pair of sides, said method comprising the steps of:

providing an end stop arrangement including a post having first and second ends;  
inserting said post through said first and second tracks near said end of said zipper; and  
after said post is inserted through said first and second tracks, forming enlarged heads on said respective first and second ends to retain said post on said zipper, said enlarged heads being disposed on opposite sides of said zipper.

17. The method of claim 16, wherein said post is inserted through said first and second profiles.

18. The method of claim 16, wherein said first track includes a first fin extending downward from said first profile and said second track includes a second fin extending downward from said second profile, and wherein said first post is inserted through said first and second fins.

19. The method of claim 18, further including the step of sealing said first and second fins to each other where said post is subsequently inserted.

20. The method of claim 16, wherein at least said first end of said post is pointed, and wherein said step of inserting said post through said first and second tracks includes piercing said first and second tracks with said pointed first end.

1/2









FIG. 2

FIG. 3

2/2



# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/US 97/14296

**A. CLASSIFICATION OF SUBJECT MATTER**  
IPC 6 A44B19/16

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)  
IPC 6 A44B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 505 057 A (MOBIL OIL CORP) 23 September 1992 see abstract; figure 2 ---	1-20
A	US 5 482 375 A (RICHARDSON DALE S ET AL) 9 January 1996 cited in the application see abstract; figures ---	1-20
A	US 4 703 518 A (AUSNIT STEVEN) 27 October 1987 see abstract; figures ---	1-20
A	EP 0 505 059 A (MOBIL OIL CORP) 23 September 1992 cited in the application see abstract; figures & US 5 067 208 A -----	1-20

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

\* Special categories of cited documents :

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*&\* document member of the same patent family

Date of the actual completion of the international search

19 November 1997

Date of mailing of the international search report

03.12.97

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel: (+31-70) 340-2040, Tx. 31 651 epo nl  
Fax: (+31-70) 340-3016

Authorized officer

Kock, S

# INTERNATIONAL SEARCH REPORT

Information on patent family members

Intern. Appl. Application No

PCT/US 97/14296

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0505057 A	23-09-92	US 5131121 A AT 145527 T AU 642589 B AU 1280092 A CA 2062569 A DE 69215409 D DE 69215409 T ES 2097276 T JP 5091909 A	21-07-92 15-12-96 21-10-93 24-09-92 23-09-92 09-01-97 27-03-97 01-04-97 16-04-93
US 5482375 A	09-01-96	US 5405478 A	11-04-95
US 4703518 A	27-10-87	US 4682366 A CA 1279038 A FR 2588246 A JP 62047303 A US 4807300 A	21-07-87 15-01-91 10-04-87 02-03-87 21-02-89
EP 0505059 A	23-09-92	US 5067208 A AT 141139 T AU 645665 B AU 1280692 A CA 2062592 A DE 69212676 D DE 69212676 T FS 2093191 T JP 5137607 A	26-11-91 15-08-96 20-01-94 24-09-92 23-09-92 19-09-96 02-01-97 16-12-96 01-06-93